DigiCert

Certification Practices Statement

DigiCert, Inc.
Version 5.16
May 30, 2023
2801 N.
Thanksgiving Way
Suite 500
Lehi, UT 84043
USA
Tel: 1-801-877-2100
Fax: 1-801-705-0481
www.digicert.com

Table of Contents

1. INTRODUCTION 7
1.1. OVERVIEW 7
1.2. DOCUMENT NAME AND IDENTIFICATION 8
1.3. PKI PARTICIPANTS 11
1.3.1. Certification Authorities 11
1.3.2. Registration Authorities and Other Delegated Third Parties 11
1.3.3. Subscribers 11
1.3.4. Relying Parties 12
1.3.5. Other Participants 12
1.4. CERTIFICATE USAGE 12
1.4.1. Appropriate Certificate Uses 12
1.4.2. Prohibited Certificate Uses 13
1.5. POLICY ADMINISTRATION 14
1.5.1. Organization Administering the Document 14
1.5.2. Contact Person 14
Revocation Reporting Contact Person 14
1.5.3. Person Determining CPS Suitability for the Policy 14
1.5.4. CPS Approval Procedures 14
1.6. DEFINITIONS AND ACRONYMS 15
1.6.1. Definitions 15
1.6.2. Acronyms 16
1.6.3. References 17
2. PUBLICATION AND REPOSITORY RESPONSIBILITIES 18
2.1. REPOSITORIES 18
2.2. PUBLICATION OF CERTIFICATION INFORMATION 18
2.3. TIME OR FREQUENCY OF PUBLICATION 18
2.4. ACCESS CONTROLS ON REPOSITORIES 18
3. IDENTIFICATION AND AUTHENTICATION 19
3.1. NAMING 19
3.1.1. Type of Names 19
3.1.2. Need for Names to be Meaningful 19
3.1.3. Anonymity or Pseudonymity of Subscribers 19
3.1.4. Rules for Interpreting Various Name Forms 19
3.1.5. Uniqueness of Names 19
3.1.6. Recognition, Authentication, and Role of Trademarks 20
3.2. INITIAL IDENTITY VALIDATION 20
3.2.1. Method to Prove Possession of Private Key 20
3.2.2. Authentication of Organization Identity and Domain/Email Control 20
3.2.2.1 Verification of IP Address 25
3.2.2.2 Wildcard Domain Validation 26
3.2.2.3 Verification of Country 26
3.2.3. Authentication of Individual Identity 27
3.2.3.1. Authentication for Role-based Client Certificates 30
3.2.3.2. Authentication of Devices with Human Sponsors 31
3.2.4. Non-verified Subscriber Information 31
3.2.5. Validation of Authority 31
3.2.6. Criteria for Interoperation 32
3.3.1. Identification and Authentication for Routine Re-key 32
3.4. IDENTIFICATION AND AUTHENTICATION FOR REVOCATION REQUEST 33
4. CERTIFICATE LIFE-CYCLE OPERATIONAL REQUIREMENTS 34
4.1. CERTIFICATE APPLICATION 34
4.1.1. Who Can Submit a Certificate Application 34
4.1.2. Enrollment Process and Responsibilities 34
4.2. CERTIFICATE APPLICATION PROCESSING 34
4.2.1. Performing Identification and Authentication Functions 34
4.2.2. Approval or Rejection of Certificate Applications 35
4.2.3. Time to Process Certificate Applications 36
4.3. CERTIFICATE ISSUANCE 36
4.3.1. CA Actions during Certificate Issuance 36
4.3.2. Notifications to Subscriber by the CA of Issuance of Certificate 36
4.4. CERTIFICATE ACCEPTANCE 36
4.4.1. Conduct Constituting Certificate Acceptance 36
4.4.2. Publication of the Certificate by the CA 36
4.4.3. Notification of Certificate Issuance by the CA to Other Entities 36

6.3.1. Public Key Archival 62
6.3.2. Certificate Operational Periods and Key Pair Usage Periods 62
6.4. ACTIVATION DATA 63
6.4.1. Activation Data Generation and Installation 63
6.4.2. Activation Data Protection 63
6.4.3. Other Aspects of Activation Data 63
6.5. COMPUTER SECURITY CONTROLS 64
6.5.1. Specific Computer Security Technical Requirements 64
6.5.2. Computer Security Rating 64
6.6. LIFE CYCLE TECHNICAL CONTROLS 64
6.6.1. System Development Controls 64
6.6.2. Security Management Controls 65
6.6.3. Life Cycle Security Controls 65
6.7. NETWORK SECURITY CONTROLS 65
6.8. TIME-STAMPING 65
7. CERTIFICATE, CRL, AND OCSP PROFILES 66
7.1. CERTIFICATE PROFILE 66
7.1.1. Version Number(s) .....

If any inconsistency exists between this CPS and the normative provisions of the foregoing policies, guidelines, and requirements ("Applicable Requirements"), then the Applicable Requirements take precedence over this CPS.

22-May-2020	Several small editorial changes made throughout the document.	5.2
27-March-2020	Added modifications to include the Level 3 NIST LOA certificates in accordance with NIST 800-63-3. Added new validation methods introduced with CABF B.R. 1.6.8 and deprecated one method. Added modifications to table 6.3.2.	

The OID

Subscribers are not always the party identified in a Certificate, such as when Certificates are issued to an organization's employees. The *Subject* of a Certificate is the party named in the Certificate. A *Subscriber*, as used herein, may refer to the Subject of the Certificate and the entity that contracted with DigiCert for the Certificate's issuance. Prior to verification of identity and issuance of a Certificate, a Subscriber is an *Applicant*.

CAs are technically also subscribers of certificates within the DigiCert Public PKI, either as the primary Certificate Authority issuing a self- signed Certificate to itself, or as an Issuer CA issued a Certificate by a superior CA. References to "end entities" and "subscribers" in this CPS, however, apply only to end-user Subscribers.

1.3.4. Relying Parties

Relying Parties are entities that act in reliance on a Certificate and/or digital signature issued by DigiCert. Relying parties must check the appropriate CRL or OCSP response prior to relying on information featured in a Certificate. The location of the CRL distribution point is detailed within the Certificate. A Relying party may, or may not also be a Subscriber of the DigiCert Public PKI hierarchy.

1.3.5. Other Participants

This CPS covers several different types of end entity Certificates/tokens with varying levels of assurance. The following table provides a brief description of the appropriate uses of each. The descriptions are for guidance only and are not binding.

Certificate	Appropriate Use
DV SSL/TLS Server Certificates	Used to secure online communication where the risks and consequences

1.5.1. Organization

DCPA determines whether an amendment to this CPS is consistent with the CP, requires notice, or an OID change. *See also* section 9.10 and section 9.12 below.

1.6.1. Definitions

"Applicant" means an entity applying for a Certificate.

"Application Software Vendor" means a software developer whose software displays or uses DigiCert Certificates and distributes DigiCert's root Certificates.

"CAB Forum" is defined in section 1.1.

"Certificate" means an electronic document that uses a digital signature to bind a Public Key and an identity.

"Certificate Approver" is defined in the EV Guidelines.

"Certificate Requester" is defined in the EV Guidelines.

"Contract Signer" is defined in the EV Guidelines.

"Direct Address" means an email address conforming to the Applicability Statement for Secure Health Transport.

"Direct Address Certificate" means a Certificate containing an entire Direct Address.

"Direct Organizational Certificate" means a Certificate containing only the domain name portion of a Direct Address.

"Domain Name" is as defined in the Baseline Requirements.

"EV Guidelines" is defined in section 1.1.

"Key Pair" means a Private Key and associated Public Key.

"OCSP Responder" means an online software application operated under the authority of

¿ îñl0o Ð"O ñ •àa''äài)? à ™.Y0" 0 " ?9–ñ s†ŽS ¡.O''à îÞ@ ±™o ¹A D 6v• aÎ As†ŽS —S Œ©• ' ¡ ëñ™o IB—S Êà y.ñ !@S

“Subscriber Agreement” means an agreement that governs the issuance and use of a Certificate that the Applicant must read and accept before receiving a Certificate.

“WebTrust” means the current version of CPA Canada’s WebTrust Program for Certification Authorities.

“WHOIS” Information retrieved directly from the Domain Name Registrar or registry operator via the protocol, the Registry Data Access Protocol, or an HTTPS website.

1.6.2. Acronyms

AATL	Adobe Approved Trust List
CA	Certificate Authority or Certification Authority
CAA	Certification Authority Authorization
CAB	”CA/Browser” as in “CAB Forum”
CMS	Card Management System
CP	Certificate Policy
CPS	Certification Practice Statement
CRL	Certificate Revocation List
CSR	Certificate Signing Request
CT	Certificate Transparency
DBA	Doing Business As (also known as "Trading As")
DCPA	DigiCert Policy Authority
DNS	Domain Name Service
DV	Domain Validated
ETSI	European Telecommunications Standards Institute
EU	European Union
EV	Extended Validation
FIPS	(US Government) Federal Information Proce00004minsgPSt15(P)6(n)]4dards

SAN	Subject Alternative Name
SHA	Secure Hashing Algorithm

2. PUBLICATION AND REPOSITORY RESPONSIBILITIES

DigiCert makes its root Certificates, revocation data for issued digital Certificates, CPs, CPSs, Relying Party

3.

DV SSL/TLS Server Certificates	DigiCert validates the Applicant's right to use or control each domain name that will be listed in the Subject Alternative Name field of a Certificate by using at least one of the

response using the Random Value, performed in accordance with BR section 3.2.2.4.4;

5. (BR section 3.2.2.4.5) is no longer used because it is deprecated as of 1-August-2018;

6. (BR section 3.2.2.4.6) is no longer used because it is deprecated as of 24-April-2020204.89 103.34 310.97 616.18 re

for each authorized Domain Name, performed in accordance with BR section 3.2.2.4.15;

16. Confirming the Applicant's control over the FQDN by calling the DNS TXT Record Phone Contact's phone number and obtaining a confirming response to validate the authorized Domain Name. Each phone call can confirm control of multiple authorized Domain Names provided that the same DNS TXT Record Phone Contact phone number is listed for each authorized Domain Name being verified and they provide a confirming response for each authorized Domain Name, performed in accordance with BR section 3.2.2.4.16;
17. Confirming the Applicant's control over the FQDN by calling the DNS CAA Phone Contact's phone number and obtain a confirming response to validate the ADN. Each phone call can confirm control of multiple ADNs provided that the same DNS CAA Phone Contact phone number is listed for each ADN being verified and they provide a confirming response for each ADN, performed in accordance with BR section 3.2.2.4.17;
18. Confirming the Applicant's control over the FQDN by verifying that the Request Token or Random Value is contained in the contents of a file (such as a Request Token, Random Value that does not appear in the request used to retrieve the file and receipt of a successful HTTP 2xx status code response from the request) performed in accordance with BR section 3.2.2.4.18; and
19. Confirming the Applicant's control over a FQDN by validating domain control of the FQDN using the ACME HTTP Challenge method defined in section 8.3 of RFC

(e

IV and OV SSL/TLS Server, Object Signing, and Device Certificates (excluding device Certificates issued under the Grid-only arc)	DigiCert validates the Applicant's right to use or control the Domain Name(s) and the country code that will be listed in the Certificate using the DV SSL/TLS Server Certificate validation procedures above. DigiCert also verifies the identity and address of the Applicant using the procedures found in section 3.2.2 or section 3.2.3 of the Baseline Requirements. DigiCert verifies any DBA included in a Certificate using a third party or government source, attestation letter, or reliable form of identification in accordance with section 3.2.2 of the Baseline Requirements.
Device Certificates issued under the Grid-only arc EV SSL/TLS Server and EV Code Signcluded	An RA or Trusted Agent validates the applicant's information in accordance with an RPS (or similar document) applicable to the community of interest.

Before issuing an SSL/TLS Server Certificate with a domain name that has not been previously verified as within the scope of an RA's or other Delegated Third Party's allowed domain names, DigiCert establishes that the RA or Delegated Third Party has the right to

Before issuing a certificate with a wildcard character (*)

3.2.3. Authentication of Individual Identity

If a Certificate will contain the identity of an individual, then DigiCert or an RA validates the identity of the individual using the following procedures:

Certificate	Validation
IV (Individual Validated) SSL/TLS Server Certificates and Object Signing Certificates (issued to an individual)	1. a. DigiCert or the RA obtains and reviews a legible copy, which discernibly shows the Applicant's face, of at least one currently valid government-issued photo ID

Level 3 Client Certificates	In-person proofing[4] before an RA, Trusted Agent, or an entity certified by a state, federal, or national entity that is authorized to confirm identities[5]. The information must be collected and stored in a secure manner. Required identification consists of one unexpired Federal/National Government-issued Picture I.D. (e.g. a passport), a REAL ID, or two unexpired Non-Federal Government I.D.s, one of which must be a photo I.D. Acceptable forms of government ID include a driver's license, state-issued photo ID card, passport, national identity card, permanent resident card, trusted traveler card, tribal ID, military ID, or similar photo identification document. See e.g. USCIS Form I-9. The person performing identity proofing examines the credentials and determines whether they are authentic and unexpired and checks the provided information (name, date of birth, and current address) to ensure legitimacy. DigiCert also employs the in-person antecedent process to meet this in-person identity proofing requirement. Under this definition, historical in-person identity proofing is sufficient if (1) it meets the thoroughness and rigor of in-person proofing described above, (2) supporting ID proofing artifacts exist to substantiate the antecedent relationship, and (3) mechanisms are in place that bind the individual to the asserted identity. In one use case, the Applicant (e.g. an employee) has been identified previously by an employer using USCIS Form I-9 and is bound to the asserted identity remotely through the use of known attributes or shared secrets. In another use case, DigiCert uses a third party Identity Verification Provider that constructs a real-time, five-question process, based on multiple historic antecedent databases.

Level 4 Client Certificates (Biometric ID Certificates)	In-

DigiCert issues Level 1, 2, 3 or 4 Client Certificates for use on computing or network devices, provided that the entity owning the device is listed as the subject. In all cases, the device has a human sponsor who provides:

Equipment identification (e.g., serial number) or service name (e.g., DNSname);
Equipment Public Keys;
Equipment authorizations and attributes (if any are to be included in the Certificate); and
Contact information.

If the Certificate's sponsor changes, the new sponsor is required to review the status of each device to ensure it is still authorized to receive Certificates. Each sponsor is required to provide proof that the device is still under the sponsor's control or responsibility on request. Sponsors are contractually obligated to notify DigiCert if the equipment is no longer in use, no longer under their control or responsibility, or no longer requires a Certificate. All registration is verified commensurate with the requested certificate type.

3.2.4. Non-verified Subscriber Information

DigiCert verifies all certificate information in accordance with industry standards.

3.2.5. Validation of Authority

The authorization of a certificate request is verified as follows:

Certificate	Verification
DV SSL/TLS Server Certificate	The authority of the requester is verified by using one or more of the procedures listed in section 3.2.2.4. of the Baseline Requirements.
OV SSL/TLS Server Certificates	The request is verified using a Reliable Method of Communication, in accordance with section 3.2.5 of the Baseline Requirements.
EV Certificates	The request is verified in accordance with section 11.8 of the EV Guidelines.
Object Signing Certificates	If the Certificate names an organization, the requester's contact information is verified with an authoritative source within the applicant's organization using a Reliable Method of Communication. The contact information is then used to

3.3.2. Identification and Authentication for Re-key After Revocation

DigiCert does not re-key after revocation. The Subscriber must undergo initial validation as specified in section 3.2.

DigiCert or an RA authenticates all revocation requests. DigiCert may authenticate revocation requests by referencing the Certificate's Public Key, regardless of whether the

Effective 2021-10-01, for validation of Domain Names and IP Addresses according to section 3.2.2.4 and 3.2.2.5 of the CAB Forum Baseline Requirements, any reused data, document, or completed validation is obtained no more than 398 days prior to issuing the Certificate

Prior to issuing a publicly-trusted SSL/TLS Server Certificate, DigiCert checks the DNS for the existence of a CAA record for each dNSName in the

and requirements found herein.

4.6.4. Notification of New Certificate Issuance to

Subscriber's Private Key based on the Public Key in the Certificate (such as a Debian weak key, see https://wiki.debian.org/SSLkeys) (CRLReason #1, keyCompromise);or

5. DigiCert obtains evidence that the validation of domain authorization or control for any FDQN or IP address in the Certificate should not be relied upon (CRLReason #4, superseded).

DigiCert may revoke a certificate within 24 hours and will revoke a Certificate within 5 days after receipt and confirming that one or more of the following occurred:

1. The Certificate no longer complies with the requirements of sections 6.1.5 and 6.1.6 of the CAB forum baseline requirements or any section of the Mozilla Root Store policy (CRLReason #4, superseded);
2. DigiCert obtains evidence that the Certificate was misused and/or used outside the intended purpose as indicated by the relevant agreement (CRLReason #9, privilegeWithdrawn);
3. The Subscriber or the cross-certified CA breached a material obligation under the CP, this CPS, or the relevant agreement (CRLReason #9, privilegeWithdrawn);
4. DigiCert confirms any circumstance indicating that use of a FQDN, IP address, or email address in the Certificate is no longer legally permitted (e.g. a court or arbitrator has revoked a Domain Name registrant's right to use the Domain Name, a relevant licensing or services agreement between the Domain Name registrant and the Applicant has terminated, or the Domain Name registrant has failed to renew the Domain Name) (CRLReason #5, cessationOfOperation)
5. For code signing, the Application Software Supplier requests revocation and DigiCert does not intend to pursue an alternative course of action;
6. For code signing, the certificate is being used to sign Suspect Code;
7. DigiCert confirms that a Wildcard Certificate has been used to authenticate a fraudulently misleading subordinate FQDN (CRLReason #9, privilegeWithdrawn);
8. DigiCert confirms a material change in the information contained in the Certificate (CRLReason #9, privilegeWithdrawn);

6. For Adobe Signing

outlined as revocation in the FBCA CP. For all other Certificate types, not

A Subscriber's subscription service ends if its Certificate expires or is revoked or if the applicable Subscriber Agreement expires without renewal.

4.12.1. Key Escrow and Recovery Policy and Practices

DigiCert never escrows CA Private Keys under this CPS.

DigiCert may escrow Subscriber key management keys to provide key recovery services. If done, DigiCert encrypts and protects escrowed Private Keys using the same or a higher level of security as used to generate and deliver the Private Key. Enterprise customers utilizing key escrow software provided by DigiCert may escrow keys within their or DigiCert's infrastructure.

DigiCert or Issuer CAs allow Subscribers and other authorized entities to recover escrowed (decryption) Private Keys. DigiCert and Issuer CAs use trusted personnel vetted per section 5.3 of the CP and this CPS during key recovery to prevent unauthorized access to a Subscriber's escrowed Private Keys. DigiCert accepts key recovery requests:

5.1.3. Power and Air Conditioning

Data centers have primary and secondary power supplies that ensure continuous and uninterrupted access to electric power. Uninterrupted power supplies (UPS) and generators provide redundant backup power.

5.1.4. Water Exposures

The cabinets housing DigiCert's CA and TSA systems are designed to prevent and protect against water exposure.

5.1.5. Fire Prevention and Protection

The data centers are equipped with fire suppression mechanisms.

5.1.6. Media Storage

DigiCert protects its media from accidental damage, environmental hazards, and unauthorized physical access. Backup files are created on a daily basis. DigiCert's backup files are maintained separately from DigiCert's primary data operations facility.

5.1.7. Waste Disposal

All unnecessary copies of printed sensitive information are shredded on-site before disposal. All electronic media are physically destroyed or are overwritten multiple times to prevent the recovery of the data.

5.1.8. Off-site Backup

DigiCert makes regular backup copies of any information necessary to recover from a system failure. Backup copies of CA Private Keys and activation data are stored for disaster recovery purposes off-site and are accessible only by trusted personnel.

5.1.9. Certificate Status Hosting, CMS and External RA Systems

All physical control requirements under section 5.1 apply equally to any Certificate Status Hosting, CMS, or external RA system.

5.2.1. Trusted Roles

Personnel acting in trusted roles include CA, TSA, and RA system administration personnel, and personnel involved with identity vetting and the issuance and revocation of Certificates. The functions and duties performed by persons in trusted roles are distributed so that one person alone cannot circumvent security measures or subvert the security and trustworthiness of the PKI or TSA operations. A list of personnel appointed to trusted roles is maintained and reviewed annually.

The CA Administrator installs and configures the CA software, including key generation, key backup, and key management. The CA Administrator performs and securely stores regular system backups of the CA system. Administrators do not issue Certificates to Subscribers.

The Registration Officer role is responsible for issuing and revoking Certificates.

The System Administrator / System Engineer installs and configures system hardware, including servers, routers, firewalls, and network configurations. The System Administrator / System Engineer also keeps critical systems updated with software patches and other maintenance needed for system stability and recoverability.

Internal Auditors are responsible for reviewing, maintaining, and archiving audit logs and performing or overseeing internal compliance audits to determine if DigiCert is operating in accordance with this CPS or an RA's Registration Practices Statement.

5.4.1. Types of Events Recorded

conditions, including any evidence of malicious activity,

DigiCert also routinely Assesses the sufficiency of the policies, procedures, information systems, technology, and other arrangements that DigiCert has in place to counter such threats.

DigiCert's Internal Auditors review the security audit data checks for continuity. DigiCert's audit log monitoring tools alert the appropriate personnel of any events, such as repeated failed actions, requests for privileged information, attempted access of system files, and unauthenticated responses.

DigiCert complies with all record retention policies that apply by law and retrieved as necessary by request of authorized parties. DigiCert includes sufficient detail in all archived records to show that

a secure electronic method or courier, or it may also refuse to provide the information in its discretion and may require prior payment of all costs associated with the data.

Key changeover procedures enable the smooth transition from expiring CA Certificates to new CA

parties at the earliest feasible time.

5.7.4 Business Continuity Capabilities after a Disaster

To maintain the integrity of its services, DigiCert implements data backup and recovery procedures as part of its Business Continuity Management Plan (BCMP). Stated goals of the BCMP are to ensure that certificate status services be only minimally affected by any disaster involving DigiCert's primary facility and that DigiCert be capable of maintaining other services or resuming them as quickly as possible following a disaster. DigiCert reviews, tests, and updates the BCMP and supporting procedures at least annually.

DigiCert's systems are redundantly configured at its primary facility and are mirrored at a separate, geographically diverse location for failover in the event of a disaster. If a disaster causes DigiCert's primary CA or TSA operations to become inoperative, DigiCert will re-initiate its operations at its secondary location giving priority to the provision of certificate status information and time stamping capabilities, if affected.

Unless otherwise addressed in an applicable agreement between DigiCert and a counterparty, before terminating its CA or TSA activities, DigiCert may:

1. Provide notice and information about the termination by sending notice by email to its customers, Application Software Vendors, and cross-certifying entities and by posting such information on DigiCert's web site; and
2. Transfer a1f[(A)-3(p)14(p)14(l)-5(i)13(c)7(a)6(t)13(iT54* nBT/F1 9.96 Tf1 0 0 1 142.7 475.15 Tm0 g0 G[( )] TJETQq0.00

6.1.4. CA Public Key Delivery to Relying Parties

DigiCert's Public Keys are provided to Relying Parties as specified in a certificate validation or path discovery policy file, as trust anchors in commercial browsers and operating system root store, and/or as roots signed by other CAs. All accreditation authorities supporting DigiCert Certificates and all application

Private Keys corresponding to Root CA Certificates are not used to sign Certificates except in the following cases:

1. Self-signed

Rudimentary	N/A	FIPS 140-2 Level 1 (Hardware or Software)
Level 1 - Rudimentary	N/A	FIPS 140-2 Level 1 (Hardware or Software)
Level 2 – Basic	FIPS 140-2 Level 1 (Hardware or Software)	FIPS 140-2 Level 1 (Hardware or Software)
Level 3 - Medium	FIPS 140-2 Level 1 (Software) FIPS 140-2 Level 2 (Hardware)	FIPS 140-2 Level 2 (Hardware)

FIPS 140-2

Medium

- Key creation, storage, and usage of Private Key must remain within the security boundaries of the cloud solution's Hardware Crypto Module that conforms to the specified requirements in this section;
- Subscription at the level that manages the Private Key must be configured to log all access, operations, and configuration changes on the resources securing the Private Key.
- Subscriber uses DigiCert's Signing Service.

6.2.2. Private Key (n out of m) Multi-Person Control

DigiCert's authentication mechanisms are protected securely when not in use and may only be accessed by actions of multiple trusted persons.

Backups of CA Private Keys are securely stored off-site and require two-person access. Re-activation of a backed-up CA Private Key (unwrapping) requires the same security and multi-person control as when performing other sensitive CA Private Key operations.

6.2.3. Private Key Escrow

DigiCert does not escrow its CA signature keys. DigiCert may provide escrow services in order

Subscribers are solely responsible for protecting their Private Keys in a manner commensurate with the Certificate type. Subscribers should use a strong password or equivalent authentication method to prevent unauthorized access or use of the Subscriber's Private Key. Subscribers should also take commercially reasonable measures for the physical protection of their workstation to prevent use of the workstation and its associated private key without the Subscriber's authorization. When deactivated, private keys shall be kept in encrypted form only and secured. At a minimum, Subscribers are required to authenticate themselves to the cryptographic module before activating their Private Keys. *See also* section 6.4.

6.2.9. Method of Deactivating Private Keys

DigiCert's Private Keys are deactivated via logout procedures on the applicable HSM device when not in use. DigiCert never leaves its HSM devices in an active unlocked or unattended state.

Subscribers should deactivate their Private Keys via logout and removal procedures when not in use.

6.2.10. Method of Destroying Private Keys

DigiCert personnel, acting in trusted roles, destroy CA, RA, and status server Private Keys when no longer needed. Subscribers shall destroy their Private Keys when the corresponding Certificate is revoked or expired or if the Private Key is no longer needed.

DigiCert may destroy a Private Key by deleting it from all known storage partitions. DigiCert also zeroizes the HSM device and associated backup tokens according to the specifications of the hardware manufacturer. This reinitializes the device and overwrites the data with binary zeros. If the zeroization or re-initialization procedure fails, DigiCert will crush, shred, and/or incinerate the device in a manner that destroys the ability to extract any Private Key.

6.2.11. Cryptographic Module Rating

See section 6.2.1.

6.3.1. Public Key Archival

DigiCert archives copies of Public Keys in accordance with section 5.5.

6.3.2. Certificate Operational Periods and Key Pair Usage Periods

DigiCert Certificates have maximum validity periods of:

Type	Private Key Use[5]	Certificate Term
Publicly Trusted Root CAs	No stipulation	25 years
Root CAs Not Otherwise Restricted	No stipulation	100 years
Publicly Trusted Sub CAs / Issuer CAs	No stipulation	15 years
IGTF Cross-certified Sub CA[6]	6 years	15 years
CRL		

by purchasing from trusted vendors as discussed above.

Updates of equipment and software are purchased or developed in the same manner as the original equipment or software and are installed and tested by trusted and trained personnel. All hardware and software essential to DigiCert's operations is scanned for malicious code on first use and periodically thereafter.

6.6.2. Security Management Controls

DigiCert has mechanisms in place to control and monitor the security-related configurations of its CA systems. When loading software onto a CA system, DigiCert verifies that the software is the correct version and is supplied by the vendor free of any modifications.

6.6.3. Life Cycle Security Controls

No stipulation.

DigiCert and RA functions are performed using networks secured in accordance with the standards documented in the DigiCert CP to prevent unauthorized access, tampering, and denial-of-service attacks. Communications of sensitive information shall be protected using point-to-point encryption for confidentiality and digital signatures for non-repudiation and authentication.

DigiCert documents and controls the configuration of its systems, including any upgrades or modifications made. DigiCert's CA system is connected to one internal network and is protected by firewalls and Network Address Translation for all internal IP addresses (e.g., 192.168.x.x). DigiCert's customer support and vetting workstations are also protected by firewall(s) and only use internal IP addresses. Root Keys are kept offline and brought online only when necessary to sign Certificate-issuing subordinate CAs, OCSP Responder Certificates, or periodic CRLs. Firewalls and boundary control devices are configured to allow access only by the addresses, ports, protocols and commands required for the trustworthy provision of PKI services by such systems.

DigiCert's security policy is to block all ports and protocols and open only ports necessary to enable CA functions. All CA equipment is configured with a minimum number of services and all unused network ports and services are disabled. DigiCert's network configuration is available for review on-site by its auditors and consultants under an appropriate non-disclosure agreement.

The system time on DigiCert's computers is updated using the Network Time Protocol (NTP) to synchronize system clocks at least once every eight hours (Windows default). All times are traceable to a real time value distributed by a UTC(k) laboratory or National Measurement Institute and are updated when a leap second occurs as notified by the appropriate body. DigiCert maintains an internal NTP server that synchronizes with cellular telephone networks and maintains the accuracy of its clock within one second or less. However, Relying Parties should be aware that all times included in a time-stamp token are synchronized with UTC within the accuracy defined in the time-stamp token itself, if present.

DigiCert will not issue a time-stamp token using any clock that is detected as inaccurate.
TST Requesters request time-stamp tokens by sending a request to DigiCert. After the TST Requester receives a response from DigiCert, it must verify the status error returned in the response. If an error was not returned, the TST Requester must then verify the fields contain0.0020hm0 612 792 reW* nBT/F1 9.96 Tf1 0 0 1 305.45 157.58

7.1.8. Policy Qualifiers Syntax and Semantics

DigiCert includes brief statements in Certificates about the

certificate subscriber's

intended to be used in the following circumstances:

- the certificate subscriber no longer controls, or is no longer authorized to use, all of the domain names in the certificate; or
- the certificate subscriber will no longer be using the certificate because they are discontinuing their website; or
- DigiCert is made aware of any circumstance indicating that use of a fully-qualified domain name or IP address in the certificate is no longer legally permitted (e.g. a court or arbitrator has revoked a domain name registrant's right to use the domain name, a relevant licensing or services agreement between the domain name registrant and the applicant has terminated, or the domain name registrant has failed to renew the domain name).

Unless the keyCompromise CRLReason is being used, the CRLReason cessationOfOperation must be used when:

- the certificate subscriber has requested that their certificate be revoked for this reason; or
- DigiCert received verifiable evidence that the certificate subscriber no longer controls, or is no longer authorized to use, all of the domain names in the certificate.

Otherwise, the cessationOfOperation CRLReason must not be used.

4) affiliationChanged

The CRLReason affiliationChanged is intended to be used to indicate that the subject's name or other subject identity information in the certificate has changed, but there is no cause to suspect that the certificate's private key has been compromised.

Unless the keyCompromise CRLReason is being used, the CRLReason affiliationChanged will be used when:

- the certificate subscriber has requested that their certificate be revoked for this reason; or
- DigiCert replaced the certificate due to changes in the certificate's subject information and the CA has not replaced the certificate for the other reasons: keyCompromise, superseded, cessationOfOperation, or privilegeWithdrawn.

Otherwise, the affiliationChanged CRLReason must not be used.

5) superseded

The CRLReason superseded is intended to be used to indicate when:

- the certificate subscriber has requested a new certificate to replace an existing certificate; or
- DigiCert obtains reasonable evidence that the validation of domain authorization or control for any fully-qualified domain name or IP address in the certificate should not be relied upon; or
- DigiCert revoked the certificate for compliance reasons such as the certificate does not comply with the DigiCert CP, this CPS, the CAB Forum's Baseline Requirements, or the Mozilla Root Store Policy.

Unless the keyCompromise CRLReason is being used, the CRLReason superseded must be used when:

8 COMPLIANCE AUDIT AND OTHER ASSESSMENTS

The practices in this CPS are designed to meet or exceed the requirements of generally accepted industry standards, including the latest versions of the WebTrust Programs for Certification Authorities as required by the Mozilla Root Store policy and other programs listed in section 1.1 and 1.6.3.

DigiCert receives an annual period in time audit by an independent external auditor to assess DigiCert's compliance with this CPS, referenced requirements, any applicable CPs, and the WebTrust for CA programs criteria.

WebTrust auditors must meet the requirements of section 8.2 of the CAB Forum Baseline Requirements and section 3.1 of the Mozilla Root Store policy where applicable.

DigiCert's WebTrust / Federal PKI auditor does not have a financial interest, business relationship, or course of dealing that could foreseeably create a significant bias for or against DigiCert.

The audit covers DigiCert's business practices disclosure, the integrity of DigiCert's PKI operations, and DigiCert's compliance with this CPS and referenced requirements. The audit verifies that DigiCert is compliant with the CP, this CPS, and any MOA between it and any other PKI.

DigiCert undergoes an audit in

On at least a quarterly basis, DigiCert performs regular internal audits against a randomly selected sample of at least three percent of its SSL/TLS Server Certificates and EV Code Signing Certificates issued since the last

For EV

4. Liability related to the security, usability, or integrity of products not supplied by DigiCert, including the Subscriber's and Relying Party's hardware; or
5. Liability related to the compromise of a Subscriber's Private Key.

The limitations in this section apply to the maximum extent permitted by law and apply regardless of (i) the reason for or nature of

proceedings related to the CPS or any DigiCert product or service.

This CPS is subject to all applicable laws and regulations, including United States restrictions on the export of software and cryptography products. Subject to section 9.4.5's Notice and Consent to Use Private Information contained in Certificates, DigiCert meets the requirements of the European data protection laws and has established appropriate technical and organization measures against unauthorized or unlawful processing of personal data and against the loss, damage, or destruction of personal data.

APPENDIX A: SAMPLE OPINION LETTER

[ ]

To: DigiCert, Inc.

2801 N. Thanksgiving Way
Suite 500
Lehi, UT 84043
Email: support@digicert.com
Fax: 801-705-0481

Re: Digital Certificate for *[Exact company name of client – see footnote 1]*("Client")

This firm represents Client, who asked that I, as its [*accountant, lawyer, solicitors,*

on Client's digital certificate application and have provided this letter solely for the benefit of DigiCert in connection with Client's application for a digital certificate. No other person or entity may rely on this letter without my express written consent. This letter shall not be quoted in whole or in part, used, published or otherwise referred to or relied upon in any manner, including, without limitation, in any financial statement or other document.

Signature: _____
Print Accountant/Attorney Name: _____
Phone Number: _____
Email: _____
Firm Name: _____
Licensed in: _____
License number, if any: _____
Contact information for licensing agency where this accountant's/attorney's license information may be verified: _____

Note 1: This must be the Client's exact corporate name as registered with the relevant Incorporating Agency in the Client's Jurisdiction of Incorporation.
Note 2: A Power of Attorney from an officer of the Client who has the power to delegate authority is sufficient to establish the Client Representative's actual authority. Multiple representatives may be listed.
Note 3: In-house counsel of the Client may submit this letter if permitted by the rules of your jurisdiction.
Note 4: This letter may be submitted by mail, fax, or email.