DigiCert

FBCA Certificate Policy for EPCS and other Programs

DigiCert, Inc.
Version 1.0
May 1st, 2024
2801 N.
Thanksgiving Way
Suite 500
Lehi, UT 84043
USA
Tel: 1-801-877-2100
Fax: 1-801-705-0481
www.digicert.com

4.2 CERTIFICATE APPLICATION PROCESSING 19
4.3 CERTIFICATE ISSUANCE 20
4.4 CERTIFICATE ACCEPTANCE 20
4.5 KEY PAIR AND CERTIFICATE USAGE .....

The FPKIPA is responsible for:

- Maintaining the FBCA CP,
- Approving applications from Entities, like DigiCert, requesting cross-certification with the FBCA,
- Ensuring the legitimacy of DigiCert and the authority of designated individuals to act on behalf of DigiCert,
-

Relying Parties make risk-informed decisions when certificates are used to manage the identities of systems and users by evaluating the environment, associated threats, and vulnerabilities. This evaluation is done by the relying party and is not controlled by DigiCert or the FPKI

DigiCert Technical Support
Suite 500
2801 N. Thanksgiving Way
Lehi, UT 84043 USA

2.4 *ACCESS CONTROLS ON REPOSITORIES*

Repositories hosting CA certificates, CRLs, and pre-generated OCSP responses (if implemented) must be publicly accessible. Information not intended for public dissemination or modification must be protected.

Posted certificates, CRLs, and pre-generated OCSP responses may be replicated in additional repositories for performance enhancement.

3 IDENTIFICATION AND AUTHENTICATION

3.1 *NAMING*

3.1.1 Types of Names

This CP establishes requirements from the FBCA CP for both subject distinguished names and subject alternative names.

CA certificates must contain a non-null subject Distinguished Name (DN). All RA certificates must include a non-NULL subject DN. The FBCA CP does not restrict the types of names that

The subject name in CA certificates must match the issuer name in certificates issued by the CA, as required by [RFC 5280].

3.1.3 Anonymity or Pseudonymity of Subscribers

Subscriber certificates must not contain anonymous or pseudonymous identities.

DNs in subscriber certificates issued by DigiCert may contain a pseudonym (such as a large number) as long as name space uniqueness requirements are met.

DigiCert may issue group certificates that identify subjects by their organizational roles. Name space uniqueness requirements as described in 3.1.5 must be met.

3.1.4 Rules for Interpreting Various Name Forms

Distinguished Names in Certificates are interpreted using the X.500 series and ASN.1 syntax.

E-mail addresses are interpreted using [RFC 5322].

3.1.5 Uniqueness of Names

DigiCert enforces name uniqueness within the X.500 namespace. Name uniqueness is not violated when multiple long as name spaceen-USol475(5ts)7[( )] TJETQ 0.00000912 0 612 792 reW*nBT/F3 9.96 Tf1364.90en-USlong as en-USspac

Trusted Agent or an entity certified by a State or Federal Entity as being authorized to confirm identities; information provided must be verified to ensure legitimacy. A trust relationship between the Trusted Agent and the applicant which is based on an in-person antecedent may suffice as meeting the in-person identity proofing requirement. Credentials required are one Federal Government-issued Picture I.D., one REAL ID Act compliant picture ID[2], or two Non-Federal Government I.D.s, one of which must be a photo I.D. Any credentials presented must be unexpired.

- Verification of digitally signed messages sent from the sponsor (using certificates of equivalent or greater assurance than that being requested).
-

4. CERTIFICATE

4.2.2 Approval or Rejection of

The certificate shall be used lawfully in accordance with DigiCert's Subscriber Agreement the terms of this CP and the DigiCert FBCA CP.

All Subscribers shall protect their Private Keys from unauthorized use or disclosure by third parties and shall use their Private Keys only for their intended purpose in accordance with section 9.6.3.

Restrictions in the intended scope of usage for a private key are specified through certificate extensions, including the key usage and extended key usage extensions, in the associated certificate.

4.5.2 Relying Party Public Key and Certificate Usage

Relying Parties shall use software that is compliant with X.509 and applicable IETF PKIX standards. DigiCert shall specify restrictions on the use of a Certificate through certificate extensions and shall specify the mechanism(s) to determine certificate validity (CRLs and OCSP).

Relying Parties must process and comply with this information in accordance with their obligations as Relying Parties. A Relying Party should use discretion when relying on a Certificate and should consider the totality of the circumstances and risk of loss prior to relying on a Certificate. Relying on a digital signature or Certificate that has not been processed in accordance with applicable standards may result in risks to the Relying Party. The Relying Party is solely responsible for such risks. If the circumstances indicate that additional assurances are required, the Relying Party must obtain such assurances before using the Certificate.

4.6 *CERTIFICATE RENEWAL*

Renewing a certificate means creating a new certificate with a new serial number where all certificate subject information, including the subject public key and subject key identifier, remain unchanged.

The new certificate may have an extended validity period and may include new issuer information (e.g., different CRL distribution point, AIA and/or be signed with a different issuer key).

Once renewed, the old certificate may or may not be revoked, but must not be reused for requesting further renewals, re-keys, or modifications.

4.6.1 Circumstance for Certificate Renewal

A certificate may be renewed if the public key has not reached the end of its validity period, the associated private key has not been compromised, and the Subscriber name and attributes are unchanged. In addition, the validity period of the certificate must meet the requirements specified in Section 6.3.2 of this CP and the FBCA CP.

CA certificates and Delegated OCSP responder certificates may be renewed so Tm0 ( )3(a)-5(s)-3(s)-3(ura)-3(n)4(c)-4(

4.7.6 Publication of the Rekeyed Certificate by the CA

As specified in Section 4.4.2.

4.7.7 Notification of Certificate

4.8.7 Notification of Certificate Modification by the CA to Other Entities

As specified in Section 4.4.3.

4.9 *CERTIFICATE REVOCATION AND SUSPENSION*

Revocation requests must be authenticated. Requests to revoke a certificate may be authenticated using that certificate's associated private key, regardless of whether or not the private key has been compromised.

For Medium, and Basic Assurance, DigiCert must publish CRLs.

DigiCert must notify the FPKIPA at least two weeks prior to the revocation of a CA certificate, whenever possible. For emergency revocation, DigiCert must follow the notification procedures in Section 5.7 of this CP and the FBCA CP.

4.9.1 Circumstances for Revocation

A certificate must be revoked when the binding between the subject and the subject's public key defined within the certificate is no longer considered valid. Examples of circumstances that invalidate the binding are:

- Identifying information or affiliation components of any names in the certificate becomes invalid. Examples include
    - Subscriber no longer affiliated with sponsoring entity
    - A wild card certificate has been issued with a name where PKI Sponsor does not exercise control of the entire namespace associated with the wild card certificate.
- Privilege attributes asserted in the Subscriber's certificate are reduced.
- The Subscriber can be shown to have violated the stipulations of its Subscriber agreement.
- There is reason to believe the private key has been compromised.
- The Subscriber or other authorized party (as defined in the CPS) asks for his/her certificate to be revoked.
- The failure of DigiCert to adequately adhere to the requirements of the FBCA CP or the approved DigiCert FBCA CPS.

DigiCert must, at a minimum, revoke certificates for the reason of key compromise upon receipt of an authenticated request from an appropriate entity.

For certificates that express an organizational affiliation, DigiCert must require that the organization inform the DigiCert of any changes in the subscriber affiliation. If the affiliated organization no longer authorizes the affiliation of a Subscriber, DigiCert must revoke any certificates issued to that Subscriber containing the organizational affiliation. If an organization terminates its relationship with DigiCert such that it no longer provides affiliation information, DigiCert must revoke all certificates affiliated with that organization.

If it is determined that revocation is required, the associated certificate must be revoked and placed on the CRL. Revoked certificates must be included on all new publications of the certificate status information until the certificates expire.

4.9.2 Who Can Request Revocation

DigiCert may summarily revoke certificates it has issued. A written notice and brief explanation for the revocation must subsequently be provided to the Subscriber.

DigiCert or other authorized agency officials may request the revocation of a Subscriber's

certificate.

DigiCert must, at a minimum, accept revocation requests from subscribers. DigiCert must accept revocation requests from the Affiliated Organization named in the certificate. Requests for certificate revocation from other parties may be supported by DigiCert.

4.9.3 Procedure for Revocation Request

DigiCert must revoke certificates upon receipt of sufficient evidence of compromise or loss of the subscriber's corresponding private key.

If it is determined that a private key used to authorize the issuance of one or more certificates may have been compromised, all certificates directly or indirectly authorized by that private key since the date of actual or suspected compromise must be revoked or must be verified as appropriately issued.

4.9.4 Revocation Request Grace Period

The revocation request grace period is the time available to the subscriber within which the subscriber must make a revocation request after reasons for revocation have been identified.

In the case of key compromise, DigiCert must request revocation within one hour of confirmation.

4.9.5 Time within which CA Must Process the Revocation Request

DigiCert will revoke subscriber certificates as quickly as practical upon receipt of a proper revocation request. Revocation requests must be processed before the next CRL is published, excepting those requests validated within two hours of CRL issuance. Revocation requests validated within two hours of CRL issuance must be processed before the following CRL is published.

4.9.6 Revocation Checking Requirements for Relying Parties

Relying parties are expected to verify the validity of certificates as specified in [RFC 5280].

Use of revoked certificates could have damaging or catastrophic consequences. The matter of how often new revocation data should be obtained is a determination to be made by the Relying Party, considering the risk, responsibility, and consequences for using a certificate whose revocation status cannot be guaranteed.

4.9.7 CRL Issuance Frequency

For this CP, CRL issuance encompasses both CRL generation and publication.

CRLs must be issued periodically, even if there are no changes to be made, to ensure timeliness of information.

For all other certificate assurance levels in this CP, online CRLs are set at a maximum interval for CRL issuance of every 24 hours.

4.9.8 Maximum Latency for CRLs

DigiCert publishes CRLs within 4 hours of generation.

Furthermore, each CRL must be published no later than the time specified in the nextUpdate field of the previously issued CRL for same scope.

Note: If pre-generation of CRLs is implemented, the thisUpdate field will be the date of generation. The nextUpdate value will be beyond the date of planned publication.

4.9.9 On-line Revocation Checking Availability

OCSP services must be designed and implemented so as to provide 99% availability overall and

limit scheduled down-time to 0.5% annually, with resources sufficient to provide a response time of ten (10) seconds or less under normal operating conditions.

4.9.10 Online Revocation Checking Requirements

On-line revocation status checking is optional for relying parties. For certificates where revocation status online checking is not available, CRLs must be used.

4.9.11 Other Forms of Revocation Advertisements Available

No stipulation.

4.9.12 Special Requirements Related to Key Compromise

When a CA certificate is revoked or subscriber certificate is revoked because of compromise, or suspected compromise, of a private key, an emergency CRL must be published based on the assurance level within the maximum latency time frames for emergency CRL Issuance listed below:

- Basic, within 24 hours after the notification.
- Mediumwithin 18 hours after notification.

4.9.13 Circumstances for Suspension

No stipulation.

4.9.14 Who Can Request Suspension

No stipulation

4.9.15 Procedure for Suspension Request

No stipulation.

4.9.16 Limits on Suspension Period

No stipulation.

4.10 *CERTIFICATE STATUS SERVICES*

4.10.1 Operational Characteristics

No stipulation.

4.10.2 Service Availability

No stipulation.

4.10.3 Optional Features

No stipulation.

4.11 *END OF SUBSCRIPTION*

No Stipulation.

4.12 *KEY ESCROW AND RECOVERY*

No stipulation.

5. FACILITY, MANAGEMENT, AND OPERATIONAL CONTROLS

5.1. PHYSICAL CONTROLS

CA equipment must be protected from unauthorized access while the cryptographic module is installed and activated. DigiCert must implement physical access controls to reduce the risk of equipment tampering even when the cryptographic module is not installed and activated. CA cryptographic tokens must be protected against theft, loss, and unauthorized use.

All the physical control requirements specified below apply equally to all CAs, and any remote workstations used to administer the CAs except where specifically noted.

5.1.1 Site Location and Construction

The location and construction of the facility housing CA equipment, as well as sites housing remote workstations used to administer the CAs, must be consistent with facilities used to house high value, sensitive information. The site location and construction, when combined with other physical security protection mechanisms such as guards, high security locks, and intrusion sensors, must provide robust protection against unauthorized access to all CA equipment and records.

5.1.2 Physical Access

The CA equipment, to include remote workstations used to administer the CAs, must always be protected from unauthorized access. The security mechanisms must be commensurate with the level of threat in the equipment environment.

DigiCert adheres to the following security requirements:

- Ensure no unauthorized access to the hardware is permitted.
- Ensure all removable media and paper containing sensitive plain-text information is stored in secure containers.

The following requirements apply to DigiCert for issuing Mediumcertificates:

- Ensure manual or electronic monitoring for unauthorized intrusion at all times.
- Ensure an access log is maintained and inspected periodically.
- Require two-person physical access control to both the cryptographic module and computer systems.

Removable cryptographic modules, activation information used to access or enable cryptographic modules, and other sensitive CA equipment must be placed in secure containers when not in use. Activation data must be either memorized, or recorded and stored in a manner commensurate with the security afforded the cryptographic module, and must not be stored with the cryptographic module or removable hardware associated with remote workstations used to administer the CA.

A security check of the facility housing the CA equipment or remote workstations used to administer the CAs (operating at the Basic Assurance level or higher) must occur if the facility is to be left unattended. At a minimum, the check must verify the following:

- The equipment is in a state appropriate to the current mode of operation (e.g., that cryptographic modules are in place when “open”, and secured when “closed”; and for offline CAs, that all equipment other than the repository is shut down).
- Any security containers are properly secured.
- Physical security systems (e.g., door locks, vent covers) are functioning properly.
- The area is secured against unauthorized access.

A person or group of persons must be made explicitly responsible for making such checks.

properly, whether accidentally or maliciously. The personnel selected to fill these roles must be extraordinarily responsible or the integrity of the CA is weakened. The functions performed in these roles form the basis of trust the entire PKI. Two approaches are taken to increase the likelihood that these roles can be successfully carried out. The first ensures that the person filling the role is trustworthy and properly trained. The second distributes the functions among more than one person, so that any malicious activity would require collusion.

The requirements of this policy are defined in terms of four roles; implementing organizations may define additional roles provided the following separation of duties are enforced.

1. Administrator – authorized to install, configure, and maintain the CA, or, optionally, KED or DDS; establish and maintain system accounts; configure audit parameters; and generate PKI component keys.
2. Officer – authorized to request or approve certificate issuance and revocations.
3. Auditor – authorized to review, maintain, and archive audit logs.
4. Operator – authorized to perform system backup and recovery.

Administrators do not issue certificates to subscribers.

These four roles are employed at the CA, RA, KRS, and CSS locations as appropriate for DigiCert. Separation of duties must comply with Section 5.2.4, and requirements for two-person control with Section 5.2.2, regardless of the titles and numbers of Trusted Roles.

5.2.1.1 Registration Officers – CMS, RA, Validation and Vetting Personnel

The Registration Officer role is responsible for issuing and revoking Certificates.

5.2.2 Number of Persons Required per Task

Only one person is required per task for CAs operating at the Basic Levels of Assurance.

Two or more persons are required for the follow DigiCert CAs for the following tasks:

- CA, key generation.
- CA signing key activation.
- CA, private key backup.

Where multiparty control is required, at least one of the participants must be an Administrator. All participants must serve in a trusted role as defined in Section 5.2.1. Multiparty control for logical access must not be achieved using personnel that serve in the Auditor Trusted Role.

5.2.3 Identification and Authentication for each Role

At all assurance levels an individual must identify and authenticate him/herself before being permitted to perform any actions set forth above for that role or identity.

5.2.4 Roles Requiring Separation of Duties

Individual personnel must be specifically designated to the four roles defined in Section 5.2.1 above. Individuals may assume only one of the Officer, Administrator, and Auditor roles, but any individual may assume the Operator role. The CA, CMS, and RA software and hardware must identify and authenticate its users and must ensure that no user identity can assume both an Administrator and an Officer role, assume both the Administrator and Auditor roles, or assume both the Auditor and Officer roles. No individual may have more than one identity.

5.3 PERSONNEL CONTROLS

5.3.1 Qualifications, Experience, and Clearance Requirements

All persons filling trusted roles working on the DigiCert CA must be selected on the basis of loyalty, trustworthiness, and integrity. Each person filling those specific trusted roles must satisfy at least one of the following:

- The person must be a citizen of the country where DigiCert is located; or
- For PKIs operated on behalf of multinational governmental organizations, the person must be a citizen of one of the member countries; or

- For PKIs located within the European Union, the person must be a citizen of one of the member States of the European Union; or
- For RA personnel of DigiCert only, in addition to the above, the person may be a citizen of the country where the RA is located.

5.3.2 Background Check Procedures

DigiCert personnel must receive a favorable adjudication after undergoing a background investigation covering the following areas:

- Employment;
- Education;
- Place of residence;
- Law Enforcement; and
- References.

The period of investigation must cover at least the last five years for each area, excepting the residence check which must cover at least the last three years. Regardless of the date of award, the highest educational degree must be verified.

Adjudication of the background investigation must be performed by a competent adjudication authority using a process consistent with [Executive Order 12968] or equivalent.

If a formal clearance is the basis for background check, the background refresh must be in accordance with the corresponding formal clearance. Otherwise, the background check must be refreshed every ten years.

5.3.3 Training Requirements

All designated Trusted Role personnel performing duties with respect to the operation of the CA or RA must receive comprehensive training relevant to their duties.

Training must be conducted in the following areas:

- Security principles and mechanisms;
- All PKI software versions in use on the system;
- All PKI duties they are expected to perform;
- Disaster recovery and business continuity procedures; and
- Stipulations of the Common CP, this CP,

policy.

PKI vendors who provide any services must establish procedures to ensure that any subcontractors perform in accordance with this CP and the FBCA CPS.

5.3.8 Documentation Supplied to Personnel

Documentation sufficient to define duties and procedures for each trusted role must be provided to the personnel filling that role.

5.4 AUDIT LOGGING PROCEDURES

The objective of audit log processing is to review all actions to ensure they are made by authorized parties and for legitimate reasons.

At a minimum, audit records must be generated for all applicable events identified in Section 5.4.1 of the FBCA CP and this CP and must be available during audit reviews and third-party audits. For CAs operated in a virtual environment, audit records must be generated for all applicable events on application software and all system software layers.

Where possible, the security audit logs must be automatically collected. Where this is not possible, a logbook, paper

Auditable Event	Basic	Medium
signature, whether generated directly on the CA or generated by a related external system or process		
CERTIFICATE REVOCATION		
All records related to certificate revocation request authorization, approval and execution, whether generated directly on the CA or generated by a related external system or process	X	X
CERTIFICATE STATUS CHANGE APPROVAL		
All records related to certificate status change request authorization, approval and execution, whether generated directly on the CA or generated by a related external system or process	X	X
CA CONFIGURATION		
Any security-relevant changes to the configuration of the CA. The specific configuration items relevant to the environment in which the CA operates must be identified and documented.	X	X
ACCOUNT ADMINISTRATION		
Roles and users are added or deleted	X	X
The access control privileges of a user account or a role are modified	X	X
CERTIFICATE PROFILE MANAGEMENT		
All changes to the certificate profile	X	X
CERTIFICATE REVOCATION LIST PROFILE MANAGEMENT		
All changes to the certificate revocation list profile	X	X
MISCELLANEOUS		
Appointment of an individual to a designated Trusted Role	X	X
Installation of the Operating System	X	X
Installation of the CA	X	X
Installing hardware cryptographic modules		X
Removing hardware cryptographic modules		X

Auditable Event	Basic	Medium

files). If an automated audit system has failed, and the integrity of the system or confidentiality of the information protected by the system is at risk, operations must be suspended until the problem has been remedied.

5.4.7 Notification to Event-causing Subject

There is no requirement to notify a subject that an event was audited. Real-time alerts are neither required nor

5.5.2 Retention Period for Archive

RA operations, to include any IT systems that facilitate RA functions, must maintain relevant archives for a minimum of 3 years after RA system replacement or termination.

5.5.3 Protection of Archive

Only Auditors, as described in Section 5.2, or other personnel specifically authorized by the CA, are permitted to add or delete records from the archive. Deletion of records identified in Section 5.5.1 before the end of the retention period is not permitted under any circumstances. The contents of the archive must not be released except in accordance with Sections 9.3 and 9.4.

Archive media must be stored in a safe, secure storage facility geographically separate from the CA in accordance with its records retention policies. The transfer process between the backup environment and archive location must be documented.

In order to ensure that records in the archive may be referenced when required, the CA must do one of the following:

- Maintain the hardware or software required to process or read the archive records, or
- Define a process to transfer records to a new format or medium when the old format or medium becomes

5.7 COMPROMISE AND DISASTER RECOVERY

DigiCert must have an incident handling process, which documents any security incidents. Security incidents may include violation or threat of violation to the system, improper usage, malicious or anomalous activity and violations of the DigiCert FBCA CPS, this CP, and the FBCA CP.

5.7.1 Incident and Compromise Handling Procedures

Subscribers to repeat the initial certificate application process.

DigiCert must post a notice on its web page describing the compromise. See Section 5.7.1 for contents of the notice.

A DigiCert-appointed governing body is encouraged to also investigate and report to the FPKIPA what caused the compromise or loss.

5.7.3.2 KRS Private Key Compromise Procedures

No stipulation.

5.7.4 Business Continuity Capabilities after a Disaster

The CA repository system must be deployed to provide 24-hour, 365 day per year availability with high levels of repository reliability.

DigiCert must have recovery procedures in place to reconstitute the CA within 72 hours of failure.

In the case of a disaster whereby the CA installation is physically damaged and all copies of the CA signature key are destroyed as a result, the FPKIPA must be notified at the earliest feasible time, and the FPKIPA must take whatever action it deems appropriate.

5.8 CA OR RA TERMINATION

For emergency termination, DigiCert must follow the notification procedures in Section 5.7.

In the event the decision is made to terminate FBCA operations, of termination of the FBCA operation, the following must be accomplished prior to termination:

- Revoke any issued certificates that have not expired
- Generate and publish a final long term CRL with a nextUpdate time past the validity period of all issued certificates. This final CRL must be available for all relying parties until the validity period of all issued certificates has passed.
- Once the last CRL has been issued, destroy the private signing key(s) of the FBCA.
- Transfer all archive data to an archival facility.

Entities will be given as much advance notice as circumstances permit, and attempts to provide alternative sources of interoperation will besought.

6.1.5 Key Sizes

DigiCert issues certificates according to requirements of the FPKI Common Policy in the following signatures: RSA PKCS #1, RSASSA-PSS, or ECDSA signatures; additional restrictions on key sizes and hash algorithms are detailed below. Certificates must contain 2048-, 3072-, or 4096-bit RSA keys, or 256- or 384-bit elliptic curve keys.

	CA certificates that expire on or before December 31, 2030	CA certificates that expire after December 31, 2030
Minimum Key Size	RSA: 2048 Elliptic Curve: 256	RSA: 3072 Elliptic Curve: 256
Hash Algorithm	SHA-256, SHA-384, or SHA-512	SHA-256, SHA-384, or SHA-512

	Subscriber certificates that expire on or before December 31, 2030	Subscriber certificates that expire after December 31, 2030
Minimum Key Size	RSA: 2048 Elliptic Curve: 256	RSA: 3072 Elliptic Curve: 256
Hash Algorithm	SHA-256, SHA-384, or SHA-512	SHA-256, SHA-384, or SHA-512

Use of Transport Layer Security (TLS) or another protocol providing similar security to accomplish any of the requirements of the FBCA CP and this CP must require at a minimum AES (128 bits) or equivalent for the symmetric key, and at least 2048-bit RSA or equivalent for the asymmetric keys. After December 31, 2030, use of TLS or another protocol providing similar security to accomplish any of the requirements of this CP must require at a minimum AES (128 bits) or equivalent for the symmetric key, and at least 3072-bit RSA or equivalent for the asymmetric keys.

6.1.6 Public Key Parameters Generation and Quality Checking

Public key parameters generation and quality checking must be conducted in accordance with [NIST SP 800-89]. Key validity must be confirmed in accordance with [NIST SP 800-56A].

6.1.7 Key Usage Purposes (as per X.509 v3 key usage field)

Public keys that are bound into certificates must be certified for use in signing or encrypting, but not both, except as specified below. The use of a specific key is determined by the key usage extension in the X.509 certificate.

All certificates must include a critical Key Usage extension

- Certificates to be used for authentication must set only the digitalSignature bit.
- Certificates to be used by Human Subscribers only for digital signatures must set the digitalSignature and nonRepudiation bits.
- Certificates that have the nonRepudiation bit set, must not have keyEncipherment bit or keyAgreement bit set.
- Certificates to be used for encryption (RSA) must set the keyEncipherment bit.
- Certificates to be used for key agreement (ECC) must set the keyAgreement bit.
- CA certificates must set only cRLSign and keyCertSign bits.

Keys associated with CA certificates must be used only for signing certificates and CRLs.

Keys associated with Device Subscriber certificates may be used for digital signature (including authentication), encryption, or both. Except for OCSP Responder certificates, device certificates must not assert the nonRepudiation bit.

6.2.3 Private Key Escrow

CA private keys are never escrowed.

Human Subscriber key management keys are not escrowed.

Subscriber private signature keys must not be escrowed.

Subscriber private dual use keys must not be escrowed. If a device has a separate key management key certificate, the key management private key is not escrowed.

6.2.4 Private Key Backup

All backups of CA and CSS private signature keys must be accounted for and protected under the same multi-person control as the original signature key. At least one copy of the CA private signature key must be stored off site.

For all other keys, backup, when permitted, must provide security controls consistent with the protection provided by the original cryptographic module. Backed up private signature key(s) must not be exported or stored in plaintext form outside the cryptographic module.

Private Key	Backup
CA • all applicable policies	Required
CSS • all applicable policies	Optional
Hardware Subscriber Key Management • id-fpki-certpcy-mediumHardware • id-fpki-certpcy-mediumHW-CBP	Optional
Hardware Device • id-fpki-certpcy-mediumDeviceHardware	Optional
Software Signature and Authentication • id-fpki-certpcy-basicAssurance • id-fpki-certpcy-mediumAssurance • id-fpki-certpcy-medium-CBP	Optional[3]
Software Subscriber Key Management • id-fpki-certpcy-basicAssurance • id-fpki-certpcy-mediumAssurance • id-fpki-certpcy-medium-CBP	Optional
Software Device	Optional

[3] Software Subscriber private signature keys may be backed up or copied, but must be held in the Subscriber's control.

• id-fpki-certpcy-mediumDevice	

6.2.5 Private Key Archival

CA private signature keys and Subscriber private signature keys must not be archived.

DigiCert does not maintain an archive of escrowed Subscriber private key management keys.

6.2.6 Private Key Transfer into or from a Cryptographic Module

A CA private key must not exist in plain text outside the cryptographic module.

CA and CSS C private signature keys may be exported from the cryptographic module only to perform CA key backup procedures as described in Section 6.2.4.

If any private key is transported from one cryptographic module to another, the private key must be protected using a FIPS approved algorithm and at a bit strength commensurate with the key being transported. Private keys must never exist in plaintext form outside the cryptographic module boundary.

Private or symmetric keys used to encrypt other private keys for transport must be protected from disclosure.

6.2.21 0 0 1 9p 0 1 0.00000912 0 6at a bit strength commensuromme

The protection mechanism must include a facility to temporarily lock the account, or terminate the application, after a predetermined number of failed login attempts as set forth in this CP and the DigiCert FBCA CPS.

6.4.3 Other Aspects of Activation Data

No stipulation.

6.5 COMPUTER SECURITY CONTROLS

6.5.1 Specific Computer Security Technical Requirements

For CAs and DDSs the computer security functions listed below are required. These functions may be provided by the operating system, or through a combination of operating system, software, and physical safeguards. The CA and its ancillary parts must include the following functionality (these functions pertain to all system software layers, where applicable):

integrity. If mutual authentication is shared secret based, the shared secret must be changed at least annually, must be randomly generated, and must have entropy commensurate with the cryptographic strength of certificates issued by the PKI being administered.

The CA must permit remote administration only after successful multi-factor authentication of the Trusted Role at a level of assurance commensurate with that of the CA.

6.8 TIME-STAMPING

Asserted times must be accurate to within three minutes. Electronic or manual procedures may be used to maintain system time. Clock adjustments are auditable events, see Section 5.4.1 of the FBCA CP and this CP.

7. CERTIFICATE, CRL, AND OCSP PROFILES

7.1 *CERTIFICATE PROFILE*

All other certificates must be compatible with X.509 Certificate and CRL Extensions Profile [FPKI-Prof].

7.1.1 Version Number(s)

Certificates must be of type X.509 v3 (populate version field with integer "2").

7.1.2 Certificate Extensions

For all CAs, use of standard certificate extensions must comply with [RFC 5280].

CA certificates must not include critical private extensions.

When used in Subscriber certificates, critical private extensions must be interoperable in their intended community of use.

DigiCert and Subscriber certificates may include any extensions as specified by [RFC 5280] in a certificate, but must include those extensions required by the FBCA CP and this CP. Any optional or additional extensions must not conflict with the applicable certificate and CRL profiles identified in Section 7.1

7.1.3 Algorithm Object Identifiers

Certificates issued by DigiCert must identify the signature algorithm using one of the following OIDs:

Signature Algorithm	Object Identifier
sha256WithRSAEncryption	{ iso(1) member-body(2) us(840) rsadsi(113549) pkcs(1) pkcs-1(1) 11 } (1.2.840.113549.1.1.11)
sha384WithRSAEncryption	{ iso(1) member-body(2) us(840) rsadsi(113549) pkcs(1) pkcs-1(1) 12 } (1.2.840.113549.1.1.12)
sha512WithRSAEncryption	{ iso(1) member-body(2) us(840) rsadsi(113549) pkcs(1) pkcs-1(1) 13 } (1.2.840.113549.1.1.13)
id-RSASSA-PSS	{ iso(1) member-body(2) us(840) rsadsi(113549) pkcs(1) pkcs-1(1) 10 } (1.2.840.113549.1.1.10)
ecdsa-with-SHA256	{ iso(1) member-body(2) us(840) ansi-X9-62(10045) signatures(4) ecdsa-with-SHA2 (3) 2 } (1.2.840.10045.4.3.2)
ecdsa-with-SHA384	{ iso(1) member-body(2) us(840) ansi-X9-62(10045) signatures(4) ecdsa-with-SHA2(3) 3 } (1.2.840.10045.4.3.3)
ecdsa-with-SHA512	{ iso(1) member-body(2) us(840) ansi-X9-62(10045) signatures(4) ecdsa-with-SHA2(3) 4 } (1.2.840.10045.4.3.4)
ecdsa-with-SHA224	{ iso(1) member-body(2) us(840) ansi-X9-62 (10045) signatures(4) ecdsa-with-SHA2(3) 1 }
ecdsa-with-SH256	{ iso(1) member-body(2) us(840) ansi-X9-62 (10045) signatures(4) ecdsa-with-SHA2 (3) 2 }
ecdsa-with-SHA384	{ iso(1) member-body(2) us(840) ansi-X9-62 (10045) signatures(4) ecdsa-with-SHA2(3) 3 }
ecdsa-with-SHA512[8]	{ iso(1) member-body(2) us(840) ansi-X9-62 (10045) signatures(4) ecdsa-with-SHA2(3) 4 }

The PSS padding scheme OID is independent of the hash algorithm. The hash algorithm is specified as a parameter (for details, see [PKCS#1]). Certificates must use the SHA-256 hash algorithm when generating RSASSA-PSS signatures. The following OID must be used to specify the hash in an RSASSA-PSS digital signature:

7.2.2 CRL and CRL Entry Extensions

Detailed CRL profiles addressing the use of each extension are specified in.

7.3 *OCSP PROFILE*

If implemented, Certificate Status Servers (CSS) must sign responses using algorithms designated for CRL signing.

All CSSs must accept and return SHA-1 hashes in the CertID and responderID fields. CSS may accept and return additional hash algorithms within the CertID fields. CSSs must not return any response containing a hash algorithm in the CertID that differs from the CertID in the request.

7.3.1 Version Number(s)

CSSs must use OCSP version 1.

7.3.2 OCSP Extensions

No stipulation.

requirements of this CP, the DigiCert FBCA CPS, and any relevant MOA provisions. DigiCert must proceed to make such notifications and take such actions without delay.

When the FPKIPA receives a report of audit deficiency from DigiCert, the FPKIPA may direct the FPKIMA to take additional actions to protect the level of trust in the infrastructure.

8.6 *COMMUNICATION OF RESULTS*

On an annual basis, the DCPA must submit an annual review package to the FPKIPA. This package must be prepared in accordance with the FPKI Annual Review Requirements document and includes an assertion from a voting member of the DCPA that all PKI components have been audited - including any components that may be separately managed and operated. The package must identify the versions of this

as it treats its own confidential information.

9.4 *PRIVACY OF PERSONAL INFORMATION*

9.4.1 Privacy Plan

DigiCert shall create and follow a publicly posted privacy policy that specifies how it handles personal information.

9.4.2 Information Treated as Private

DigiCert shall treat all personal information about an individual that is not publicly available in the contents of a Certificate or CRL as private information. DigiCert shall protect private information in its possession using a reasonable degree of care and appropriate safeguards. DigiCert shall not distribute Certificates that contain the UUID in the subject alternative name extension via publicly accessible repositories (e.g., LDAP, HTTP).

For DigiCert, collection of PII must be limited to the minimum necessary to validate the identity

referenced in the Certificate. DigiCert, Affiliates, and customers shall grant permission to use revocation information to perform Relying Party functions subject to the applicable CRL usage agreement, Relying Party Agreement, or any other applicable agreements.

9.5.2 Property Rights in the CP

DigiCert retains all intellectual property rights in and to this CP.

9.5.3 Property

inform DigiCert of any severance of affiliation with any current subscriber.

9.7 *DISCLAIMERS OF WARRANTIES*

Except as expressly stated otherwise herein, an applicable extended warranty protection planor as limited by law, DigiCert disclaims all warranties and obligations related to this CP.

9.8 *LIMITATIONS OF LIABILITY*

DigiCert

9.10.3 Effect of Termination and Survival

DigiCert will communicate the conditions and effect of this CP's termination via the DigiCert Repository. The communication will specify which provisions survive termination. At a minimum, responsibilities related to protecting confidential information will survive termination.

9.11 *INDIVIDUAL NOTICES AND COMMUNICATIONS WITH PARTICIPANTS*

For DigiCert, any planned change to the infrastructure that has the potential to affect the FPKI operational environment must be communicated to the FPKIPA at least two weeks prior to implementation. All new artifacts (CA certificates, CRL DP, AIA and/or SIA URLs, etc.) produced as a result of the change must be provided to the FPKIPA within 24 hours following implementation.

9.12 *AMENDMENTS*

9.12.1 Procedure for Amendment

Amendments are made by posting an updated version of the CP to the online repository upon review and approval by the DCPA while working with the FPKIPA. Updates supersede any designated or conflicting provisions of the referenced version of the CP. Controls are in place to reasonably ensure that this CP is not amended and published without the prior authorization of the DCPA working with the FPKIPA. The DCPA reviews this CP annually.

9.12.2 Notification Mechanism and Period

DigiCert will post notice on its website of any proposed significant revisions to this CP. Although DigiCert may include a final date for receipt of comments and the proposed effective date, DigiCert is not required to have a fixed notice-and-comment period. DigiCert and the DCPA reserve the right to amend the CP without notice for any reason, including without limitation corrections of typographical errors, changes to URLs, and changes to contact information. The DCPA's decision to designate amendments as material or non-material shall be within the DCPA's sole discretion.

/Artifact <

9.12.3 Circumstances under which OID Must Be Changed

If the DCPA determines an amendment necessitates a change in an OID, then the revised version of this CP will also contain a revised OID. Otherwise, amendments do not require an OID change.

9.13 *DISPUTE RESOLUTION PROVISIONS*

To the extent permitted by applicable law, Subscriber Agreements and Relying Party Agreements shall contain a dispute resolution clause. Unless otherwise approved by DigiCert, the procedure to resolve disputes involving DigiCert require an initial negotiation period of sixty (60) days followed by litigation in the federal or state court encompassing Salt Lake County, Utah, in the case of claimants who are U.S. residents, or, in the case of all other claimants, arbitration administered by the International Chamber of Commerce ("ICC") in accordance with the ICC Rules of Conciliation and Arbitration

Before resorting to any dispute resolution mechanism, including adjudication or any type of alternative dispute resolution, a party must notify DigiCert

Consent to Use Private Information contained in Certificates, each Issuer CA shall (i) be licensed